



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

MATT ENAMEL

PRODUCT DATA SHEET

Good quality Alkyd Resin Based Matt top coat for interior wood and metallic surfaces.

MATT ENAMEL is a general purpose decorative coating used as a finishing for alkyd based paint systems on all types of wood and metallic surfaces. It is easy to apply and dries rapidly to give a durable, washable matt finish.

USAGE

- On suitably primed interior & exterior wood such as beams, panels, ceilings, doors, skirting, furniture, hand rails, decorative items.
- On suitably primed interior mild steel, galvanised steel or aluminium surfaces such as doors, furniture, hand rails, balustrades.
- **MATT ENAMEL** is not suitable for surfaces which will be subjected to strong wear and tear conditions, do not use on Concrete, floors, counter and table tops.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** White, Black and Penlac Range of Colours
- **Consistency :** Semi viscosity liquid
- **Specific Gravity :** 1.19 -1.21 (approx.)

- **Flash Point :** 28 °C (Closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 4Lts, 1Lt,

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface Preparation:** Surface must be dry, clean and rust free.
- **Application method:** Apply two coats by roller or brush, or Low pressure airless spray.
-
- **Dilution:** Thin down with **TEST BENZIN** as required.
- **Spreading rate / Film thickness:** One litre of **MATT ENAMEL** will cover between 9 and 11 m² of surface in one coat; at this spreading rate the dry film thickness will vary between 53 and 44 microns on a completely smooth, non absorbent surface.
- **Drying Time:** Approximately 4 hours to touch dry, **MATT ENAMEL** can be over-coated after approximately 16 hours.
- **Cleaning Solvent:** Test Benzin.
- **Preceding Coat:** Use an alkyd based metal or wood primer as applicable, followed by Universal Undercoat.
- **Subsequent Coat:** Not required.

SAFETY

- **MATT ENAMEL** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application. Remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.