



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

RED OXIDE PRIMER

PRODUCT DATA SHEET

An Alkyd Resin Based Primer for mild steel.

- Available in Red Oxide colour.

RED OXIDE PRIMER is an economical lead free, general purpose, quick drying primer used mainly for maintenance work and for touch-up to give temporary protection. It is recommended for use in alkyd based paint systems.

USAGE

- On mild steel.
- As a touch-up primer.
- For interior and exterior use.

Note: Condensation or dew formation on metallic surfaces will result in poor adhesion and subsequent flaking of the paint. Avoid painting during early morning, late evening or during humid and wet periods.

PHYSICAL DATA

- | | |
|-----------------------------|---------------------|
| • Finish : | Matt |
| • Colour : | Red Oxide |
| • Consistency : | Semi Viscous Liquid |
| • Specific Gravity : | 1.34 (Approx.) |
| • Volume Solids : | 55 % (Approx.) |
| • Flash Point : | 38 °C, closed cup |
| • Shelf Life : | 12 months. |
| • Packing : | 20Lts, 4Lts, 1Lt |

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface preparation:** Surface must be dry, clean and Rust free.
- **Application Method:** Apply one coat by brush, roller and airless spray.
- **Dilution:** Thin down with **TEST BENZIN** as required.
- **Spreading rate / Film thickness:** One litre of **RED OXIDE METAL PRIMER** will cover between 9 and 11 m² of surface in one coat.
- **Drying Time:** Approximately 2 hours to touch dry, **RED OXIDE METAL PRIMER** can be over-coated after approximately 7 hours when cured in direct sunlight, otherwise allow to cure overnight.
- **Cleaning Solvent:** **TEST BENZIN**
- **Preceding Coat:** Not required.
- **Subsequent Coat:** Alkyd Based Enamel finish.

SAFETY

- **RED OXIDE METAL PRIMER** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.