



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

# UNIVERSAL UNDERCOAT

## PRODUCT DATA SHEET

A good quality alkyd resin based undercoat with high hiding power, good flow and durability.

- Available in White, **UNIVERSAL UNDERCOAT**.

**UNIVERSAL UNDERCOAT** applied over a primer will provide good inter-coat adhesion, good opacity and will help to fill minor irregularities. It is easy to apply, dries quickly and has good sanding properties. **UNIVERSAL UNDERCOAT** is recommended for use in alkyd based paint systems.

**Note:** Suitable for wood and most certainly **not for concrete application.**

### USAGE

- As an undercoat over alkyd based wood.
- On interior and exterior surfaces.

### PHYSICAL DATA

- **Finish :** Matt
- **Colour :** White.
- **Consistency :** Semi viscous liquid
- **Specific Gravity :** 1.6 (approx.)
- **Volume Solids :** 65% (approx.)
- **Flash Point :** 38 °C (Closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 4Lts, 1Lt,

Paints should be stirred before use and occasionally whilst in use.  
Contact your supplier for further information

## APPLICATION

- **Surface Preparation:** Surface must be dry, clean and rust free.
- **Application Method:** Apply one coat by roller, brush or Low pressure airless spray.
- **Dilution:** Thin down with **TEST BENZIN** as required.
- **Spreading rate / Film thickness:** One litre of **UNIVERSAL UNDERCOAT** will cover between 7 and 9 m<sup>2</sup> of surface in one coat.
- **Drying Time :** Approximately 2 hours to touch dry, **UNIVERSAL UNDERCOAT** can be over-coated after approximately 5 - 6 hours when cured in direct sunlight, otherwise allow to cure overnight.
- **Cleaning Solvent:** Test Benzin.
- **Preceding Coat:** Use an Alkyd based.
- **Subsequent Coat:** Alkyd Based or Emulsion Based for finishing coats.

## SAFETY

- **UNIVERSAL UNDERCOAT** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

## MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.