



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

WOOD PRIMER GREY

PRODUCT DATA SHEET

Good quality Alkyd Resin Based general purpose primer for all types of wood.

- Available in Grey.

WOOD PRIMER GREY applied directly onto the substrate will provide maximum adhesion between the substrate and subsequent coats. It is easy to apply and dries quickly to give good opacity and grain filling properties. **WOOD PRIMER GREY** is recommended for use in Alkyd based paint systems.

USAGE

- As a primer on all types on wood.
- On interior and exterior surfaces.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** Grey
- **Consistency :** Semi viscous liquid
- **Specific Gravity :** 1.53 (approx.)
- **Volume Solids :** 55% (approx.)
- **Flash Point :** 38 °C (Closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 5Lts, 1Lt

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Surface Preparation:** Surface must be dry and clean.
- **Application Method:** Apply one coat by roller, brush or airless spray.
- **Dilution:** Thin down with **TEST BENZIN** as required.
- **Spreading Rate / Film thickness:** One litre of **WOOD PRIMER GREY** will cover between 6 and 8 m² of surface in one coat.
- **Drying Time:** Approximately 2 hours to touch dry, **WOOD PRIMER GREY** can be over-coated after approximately 5 - 6 hours when cured in direct sunlight, otherwise allow to cure overnight.
- **Cleaning Solvent:** Test Benzin.
- **Preceding Coat:** Not required.
- **Subsequent Coat:** Alkyd or Emulsion Based for finishing coats.

SAFETY

- **WOOD PRIMER GREY** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.