



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

# ROAD MARKING PAINT

## PRODUCT DATA SHEET

Fast drying Alkyd Resin Based Road Marking Paint.

**ROAD MARKING PAINT** has a high resistance to abrasion, water and diesel fuel. This product is resistant to the common problem of bleeding of bitumen through to the paint surface.

### USAGE

- For marking on bituminous and concrete surface.
- For marking of centre line, curb line, pedestrian crossing and other road markings.
- For parking bays.
- For interior and exterior use.

### PHYSICAL DATA

- **Finish :** Satin
- **Colour :** White, Black & Yellow
- **Pigment:** Adequate Weather fast Pigments
- **Specific Gravity :** 0.92 (approx.)
- **Volume Solids :** 50 % (approx.)
- **Flash Point :** 28 ° C (Closed cup)
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 4Lts, 1Lt

Paints should be stirred before use and occasionally whilst in use.  
Contact your supplier for further information

## APPLICATION

- **Surface Preparation:** New concrete surfaces must be allowed to cure for at least 28 days before painting. Surfaces to be clean, dry, sound and free from obvious loose particles.
- **Application Method:** Apply one coat by Roller, Brush and Airless spray.
- **Dilution:** Not normally recommended. If necessary use **CHLORINATED RUBBER THINNER**.
- **Spreading rate / Film thickness:** One litre of **ROAD MARKING PAINT** will cover between 8 to 10 m<sup>2</sup>.
- **Drying Time:** +- 25 Min for 50m (Microns) wet film at 28°C 1 hours ( in dry warm weather.
- **Cleaning Solvent:** **CHLORINATED RUBBER THINNER**.
- **Preceding Coat:** Not required.
- **Subsequent Coat:** Not required.

## SAFETY

- **ROAD MARKING PAINT** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

## MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.