



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

EMULSION PRIMER WHITE

PRODUCT DATA SHEET

An Acrylic Based, Alkali Resistant Emulsion primer for application directly on new plastering. **EMULSION PRIMER WHITE** will penetrate the substrate to provide a basis for good adhesion of subsequent coatings.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On ceiling boards and interior panel wood.
- On absorbent wall coverings (wall paper, etc.)
- Recommended for interior and exterior use.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** White
- **Consistency :** Low viscosity liquid
- **Specific Gravity :** 1.08 (approx.)
- **Volume Solids :** 40% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 5Lts, 10Lts, 1Lt

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Application Method:** Apply one coat by brush, roller or spray onto a clean, dry surface.
- **Spreading rate / Film thickness:** One litre of **EMULSION PRIMER WHITE** will cover between 8 and 9 m² of surface in one coat.
- **Drying Time:** Approximately 40 minutes to touch dry, **EMULSION PRIMER WHITE** can be over-coated after approximately 3 hours.
- **Cleaning Solvent:** Use water; if necessary add some liquid detergent to warm water.
- **Preceding Coat:** Not required.
- **Subsequent Coat :** Emulsion Paints

SAFETY

- **EMULSION PRIMER WHITE** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.