



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

PENCRYL EMULSION INT/EXT

PRODUCT DATA SHEET

A general purpose, Decorative, exterior/interior, high quality paints for concrete surfaces with built-in fungus resistance particularly suitable sub-humid and dry regions.

USAGE

- On sealed cement substrates such as plaster, concrete and building blocks.
- On sealed panel wood and ceiling boards.
- On sealed absorbent wall coverings (wall paper, etc.)
- Recommended for interior or exterior use in dry regions and for interior use in sub-humid regions.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** White
- **Resin:** P.V.A / Acrylic Copolymer
- **Specific Gravity :** 1.40 (approx.)
- **Volume Solids :** 35% (approx.)

- **Shelf Life :** 12 months
- **Packing :** 20LtS, 10Lts, 5Lts, , 1Lt

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface Preparation** : Surface must be dry and clean
- **Application Method**: Apply three coats by Roller, Brush, Airless Spray.
- **Spreading rate / Film thickness**: One litre of **PENCRYL EMULSION** will cover between 8 and 10 m² of surface in one coat.
- **Drying Time**: Approximately 30 minutes to touch dry, **PENCRYL EMULSION** can be over-coated after approximately 3 hours.
- **Cleaning Solvent**: Use water, if necessary add some liquid detergent to warm water.
- **Preceding Coat**: Seal with **PENLAC CLEAR EMULSION BINDER** or **PENLAC PLASTER RESISTANT PRIMER** on new surface and on powdery surfaces.

SAFETY

- **PENCRYL EMULSION** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.