



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

PENTOP EMULSION

PRODUCT DATA SHEET

Top quality Pure Acrylic Resin Emulsion paint with excellent resistance to weathering, fungus, abrasion and staining.

PENTOP is a decorative and protective coating primarily selected for its exceptional performance, long life and long term economical advantage. It is recommended for decorating and protecting homes, offices, factories, shops, hotels and other related structures.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On panel wood and ceiling boards.
- On absorbent wall coverings (wall paper, etc.)
- On bituminous and tar surfaces.
On suitably primed interior wood structures.
- Recommended for interior and exterior application.

PHYSICAL DATA

- **Finish :** Matt
- **Colour :** White, Black and Range of colours
- **Resin:** Pure Acrylic Resin
- **Specific Gravity :** 1.49 (approx.)
- **Volume Solids :** 55% (approx.)
- **Flash Point :** Not Applicable
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 10Lts, 5Lts, 1lt

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information

APPLICATION

- **Application Method:** Apply three coats by roller, brush or Airless Spray onto clean, dry and sealed surface.
- **Spreading Rate / Film thickness:** One litre of **PENTOP EMULSION** will cover between 9 and 11 m² of surface in one coat; at this spreading rate the dry film thickness will vary between 40 and 50 microns on a completely smooth, non absorbent surface.
- **Drying Time:** Approximately 30 minutes to touch dry, **PENTOP EMULSION** can be over-coated after approximately 3 hours.
- **Cleaning Solvent:** Use water; if necessary add some liquid detergent to warm water.
- **Preceding Coat:** Use **PENLAC PASTER RESISTANT PRIMER** or **PENLAC CLEAR EMULSION BINDER** sealer on new cement surfaces and on powdery or absorbent surfaces.
- **Subsequent Coat:** Not required.

SAFETY

- **PENTOP** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.