



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

VIP SATIN EMULSION

PRODUCT DATA SHEET

High quality, Decorative Satin Emulsion paint for Interior and exterior walls and Ceilings.

- **VIP SATIN EMULSION** is available in white and black and in a range of Colours.

VIP SATIN EMULSION is a decorative and protective coating primarily selected for its exceptional performance, long life and long term economical advantage. It is recommended for decorating and protecting the interior of homes, offices, factories, shops, hotels and other related structures. The outstanding wash ability and scrub ability property of VIP SATIN EMULSION makes it ideal as an interior coating.

USAGE

- On cement substrates such as plaster, concrete and building blocks.
- On panel wood and ceiling boards.
- On absorbent wall coverings
- On suitably primed interior wood structures.
- Recommended for interior and exterior application.

PHYSICAL DATA

- **Finish :** Mid- Gloss Satin
- **Colour :** White, Black & range of colours.
- **Consistency :** Medium viscosity liquid
- **Specific Gravity :** 1.3 (approx.)
- **Volume Solids :** 53% (approx.)
- **Resin :** Vinyl Acrylic Resin
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 10Lts,5Lts , 1 L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Surface Preparation:** Surface must be Dry, Clean, Grease and Rust free.
-
- **Application Method:** Apply three coats by roller or brush low pressure spray equipment.
- **Spreading rate / Film thickness:** One litre of **VIP SATIN EMULSION** will cover between 6 and 8 m² of surface in one coat.
- **Drying Time:** Approximately 45 minutes to touch dry, **VIP SATIN EMULSION** can be over-coated after approximately 3 to 4 hours.
- **Cleaning Solvent:** Use water; if necessary add some liquid detergent to warm water.
- **Preceding Coat:** Use **PENLAC CLEAR EMULSION BINDER** or **PENLAC PLASTER RESISTANT PRIMER** as a sealer on new cement substrates and on powdery or absorbent surfaces.
- **Subsequent Coat** : Not required

SAFETY

- **VIP SATIN EMULSION** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.