



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

ETCH SOLUTION

PRODUCT DATA SHEET

ETCH SOLUTION is an aqueous solution of a weak acid.

USAGE

- For etching concrete surfaces to remove surface laitance prior to application of paint systems.

NOTE:- **ETCH SOLUTION** should not be used on cement based plastering's.

PHYSICAL DATA

- **Product Code :**
- **Colour :** Liquid
- **Specific Gravity :** 1.03 approximately
- **Flash Point :** > 23° C Closed cup
- **Shelf Life :** 12 months
- **Packing :** 1 L, 5 L, 20 L.

APPLICATION

- **Application method:** Apply by brush and allow to react for 10 - 15 minutes. Scrub with a stiff nylon brush to remove soiling. Wash thoroughly with fresh water.
- **Spreading rate:** Spreading rate will depend largely on porosity of the surface. Under normal circumstances, the spreading rate will be approximately 10 - 15 m².
- **Cleaning solvent:** Water.

SAFETY

- **ETCH SOLUTION** is a hazardous material and should be used with caution.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.
- A complete Material Safety Data Sheet is available on request.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

