



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

## INATEINTE

### PRODUCT DATA SHEET

**INATEINTE** is a range of solvent soluble wood stains and tints used for enhancing the appearance of wood.

- Available as a range of different base tints – Example Mahogany, Walnut, Dark Oak, Teak Brown, Black.

#### USAGE

- For tinting bare wood in the decorative and handicraft sector.
- For enhancing and improving the appearance of timber used in the furniture industry.
- As wood stains miscible with solvent based wood sealers.
- For interior use.

**Note:** **INATEINTE** dyes should not be used on timbers which are exposed to direct sunlight. They will tend to fade out.

Some tints may discolour in the short or medium term when **INATEINTE** is mixed with acidic products such as those from the **ACID CATALYSED** range. It is advisable to check for discoloration before proceeding.

#### PHYSICAL DATA

- **Finish :** Not applicable
- **Colour :** Base tints which can be mixed to produce custom colours.
- **Consistency :** Liquid
- **Specific Gravity :** 0.8 Approx.
- **Volume Solids :** Not applicable
- **Flash Point :** < 23 °C, closed cup
- **Shelf Life :** 12 months
- **Packing :** 20 L, 5 L, 1 L,

Paints should be stirred before use and occasionally whilst in use.  
Contact your supplier for further information

## APPLICATION

- **Surface preparation :** Wood Should be Clear and Dry
- **Application method:** Apply **INATEINTE** uniformly by brush, cloth pad or conventional spray onto base wood. After checking compatibility, **INATEINTE** can also be mixed to solvent based wood sealers to obtain wood stains for application by brush or conventional spray.
- **Dilution:** Not recommended. Dilute with Two pack Acrylic Thinner to lower the tinting strength if necessary.
- **Spreading rate / Film thickness:** Not applicable.
- **Drying time :** Approximately 5 - 10 minutes
- **Cleaning solvent :** Two Pack Acrylic Thinner
- **Preceding coat:** None.
- **Subsequent coat:** Any clear wood sealer or topcoat.

## SAFETY

- **INATEINTE** is flammable, keep away from ignition source. Do not smoke whilst using.
- Wear adequate protective equipment during application, remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

## MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.