



Le Rocher, Mahe, Seychelles - P.O Box 368 Tel: 4344606/108 Fax: 4344373

email: penlacadmin@seychelles.sc

PLASTER RESISTANT PRIMER

PRODUCT DATA SHEET

PLASTER RESISTANT PRIMER is designed to be used as a primer coat for new plastering. **PLASTER RESISTANT PRIMER** is slightly textured to provide grip for subsequent textured coating, it is alkali resistant and has excellent adhesion to most cementations surfaces.

USAGE

- As a primer coat on cement surface such as plaster, concrete and building blocks.
- Recommended for exterior and interior use.

PHYSICAL DATA

- **Colour :** White
- **Specific Gravity :** 1.50 (approx.)
- **Volume Solids :** 60 % (approx.)
- **Shelf Life :** 12 months
- **Packing :** 20Lts, 4Lts, 1L

Paints should be stirred before use and occasionally whilst in use.
Contact your supplier for further information.

APPLICATION

- **Application Method:** Apply one coat by roller or brush onto clean, dry and sound surface.
- **Dilution:** It is not necessary to thin down the paint for application. However, **PLASTER RESISTANT PRIMER** can be diluted with Test Benzin to suit your specific requirements.
- **Spreading rate:** Apply one coat at a spreading rate of 6 – 8 m² per litre.
- **Drying time:** Approximately 1 hour to touch dry; **PLASTER RESISTANT PRIMER** can be over-coated after approximately 2 - 3 hours.
- **Cleaning solvent:** Use Test Benzin.
- **Subsequent coat:** Emulsion Based for finishing coats.

SAFETY

- **PLASTER PRIMER** can be safely used in rooms that will be occupied the following day or where food stuff are stored or processed.
- Wear adequate protective equipment during application; remove splashes from skin with soap and water. In case of contact with eyes, rinse with ample water and seek medical advice if necessary.
- Ensure good ventilation during application and drying.
- Keep containers tightly closed and away from children.

MAINTENANCE

Surfaces prepared and painted according to specification will provide lasting protection and will facilitate maintenance. Carry out repairs as and when required and wash the surface occasionally; use mild detergent and light scrubbing to remove stains.

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.